



Dimensions: 121(D)x100(W)x110(H) mm

Features

- High power density
- Universal input range
- Built-in cooling fan
- RoHS compliance
- 3 year warranty
- Great reliability
- DIN Rail / Wall bracket mounting solution
- Redundant & Rdy Function
- Over voltage protection
- Overload protection
- Short circuit protection
- Active PFC to meet EN61000-3-2(PF>0.94)

Safety Standards



EN 60950 (Marking)



UL 508 (Certificate)
CSA 22.2 (Certificate)


EMC Standards

EN55011	Class B
EN55022	Class B
EN61000-4-2	Level 3
EN61000-4-3	Level 3
EN61000-4-4	Level 3
EN61000-4-5	Level 3
EN61000-4-6	Level 3
EN61000-4-8	Level 3
EN61000-4-11	Level 3

Model List

Model	O/P Voltage Adjustment	Min.	Rated	Max.	Ripple Noise	Efficiency	Over Voltage Protection
AD1360-12CR	+12VDC±10%	0A	30A	30A	100mVp-p	78%	15~17VDC
AD1360-24CR	+24VDC±10%	0A	15A	15A	150mVp-p	81%	27~30VDC
AD1360-30CR	+30VDC±10%	0A	12A	12A	200mVp-p	81%	35~40VDC
AD1360-48CR	+48VDC±10%	0A	7.5A	7.5A	250mVp-p	83%	52~56VDC

Model Encoding



Website: <http://www.acro-powers.com/>
E-mail: service@acro-powers.com.tw
Tel: +886-2-22675015 Fax: +886-2-22674939

ACRO
ENGINEERING INC.

Specification

General		
Switching Frequency		132kHz
Isolation Voltage	Input-Output	3000VAC /4242VDC
	Input-FG	1500VAC/2121VDC
	Output-FG	500VAC/ 710VDC
Isolation Resistance		100MΩ when Input-Output @500VDC
Operating Temperature		-40°C~50°C ambient
Derating		2.5% per degree from 50°C to 70°C
Storage Temperature		-40°C to +85°C
Relative Humidity		5%~95% RH, Non-condensing.
Temperature Coefficient		±0.04% of output voltage per °C
MTBF		60,000hrs Min. Per MIL-HDBK-217F, 25°C GB
Attitude During Operation		2000m
Installation position		Vertical
Vibration		Random Vibration, 10~500Hz. 3 axise
Input		
Input Voltage		100~240VAC/120~370VDC
Input Frequency		47~63Hz
Inrush Current (cold start)		22A/115VAC 44A/230VAC
Rated Input Current		6A Max.@Vi=100~240VAC
Leakage Current		Input-output 0.25mA, Input-FG 3.5mA, Vi=250VAC
Output		
Output Voltage accuracy		±1%
Minimun Load		0%
Line Regulation		±1%, measuring from low line to high line rated load
Load Regulation		±1%, measuring from 20% to 100% of rated load 230VAC input
Voltage Trim Range		±10%
Rated Continuous Loading		30A@12VDC, 15A@24VDC, 7.5A@48VDC
Hold Up Time		40mS Min., Full load@230VAC.
Turn On Time		1200mS
Rise Time		15mS
Fall Time		30mS

Specification


Output

Transient Response	Recovery Time	2mS, Load change 50% to 100%
	Voltage Deviation	5%, Load change 50% to 100%
Efficiency		See model list, measuring at rated load and 230VAC input
Ripple and Noise		See model list, measuring by using a 0.1 μ F/630V metalize capacitor and a 47 μ F electrolytic capacitor parallel on the test point, at rated load and 230VAC input.


Protection

Input Fuse	8A/250V
Internal Surge Load Protection	Varistor, IEC6100-4-5
Degree of Protection	IP20
Short Circuit Protection	Autorecovery
Over Voltage Protection	Autorecovery
Rated Over Load Protection	130~150%
Overload protection	Power limited

Derating Curve




Rdy & Redundant connection



P.S. Please adjust output voltage of each unit as close as possible to balance the loading.


Mechanical Details



Terminal Allocation

Designation	Description
DC OK	Green LED Indicator
V Adj.	O/P Voltage adjustment
+	Output Positive
-	Output Negative
NC	No Connect
⏏	Earth
N	Input Neutral
L	Input Line

Installation instruction



Place the top of the AD1360CR rail mount over the top of the DIN rail. Tilt the bottom of the AD1360C toward the DIN rail until it snaps into place.

To remove the AD1360CR from the DIN rail, use a flathead screwdriver to pull down the bottom of the rail mount and tilt it away from the DIN rail.

To install AD1360CR on wall/plate, loosening screws on mounting bracket and pull both brackets out first. Then re-screwing the two brackets with screws onto wall/plate.

The left housing of AD1360CR is designed as a heat sink, please keeping a minimum distance of 15mm from each other.